



ELMO PX-30E/-10E

PROFESSIONAL VISUALISER

THE ELMO IN PRACTICE

Conferences



Technical Meetings



KEY FEATURES

4K Native Output vai HDMI (PX-30E)



Shooting A3



Courtrooms



Seminars



288x Magnification, Zoom and AF Key on Camera Head



5" Touch Screen For Preview and Operation



ELMO PX series is designed for professional use.

Best for large conferences as a component of visual presentation

Best for technical seminars or TV conferences to show and share the image of 3D objects

Best for courtrooms where physical evidence is always critical

Foldable Arm



Writable Stage



Multiple Technical Interface (PX-30E)



ELMO Interactive Toolbox (EIT) Software for Windows



	PX-30E	PX-10E
Camera	77.00=	
Image Sensor	1/2.3" CMOS	
Effective Pixels	8.3M (3840x2160@16:9 aspect), 9.3M (3520x2640@4:3 aspect)	
Frame Rate	Max. 60fps@FHD, 30fps@4K	Max. 60fps
Zoom	Optical x12 + Sensor x2	•
Lens/Max Aparture	F=3.2 ~ 3.88	
Focus Range	Wide 50mm ~ ∞, Tele 200mm ~ ∞	
Focus Control	Auto (One push) / Zoom Sync / Manual / Area Focus by touch screen	
Shooting Area	470x259mm @16:9 aspect, 431×321mm @4:3 aspect Possible to shoot A3 format	
Resolution	4K (3840x2160) via HDMI	Full HD (1920x1080)
User Interface		
LCD Display	5" Touch s	screen
Zoom Key	Yes (On Stage and Camera Head)	
Auto Focus Key	Yes (On Stage and Camera Head)	
Pass-through	Yes (HDMI/RGB)	
Lighting	White LED	
Foldable Mechanical Arm	Yes	
Adjustable Arm/Head	Yes/Yes	
Integrated Stage	Yes (Writable)	
Image Rotation	90°/180°/270°	
Freeze	Yes	
Annotation	Yes by PC software	
Comparison	Yes by PC software	
Mask	Yes	
Recording	Yes (Photo/Video)	
Playback Capability	Photo : JPG Video : MP4	
Optional Apps	ELMO Interactive Toolbox (EIT) for Windo	ws, Available at www.elmoeurope.com
Technical Interface		
USB	x2 (Type A, Version 2.0), x1 (Type B, Version 3.0)	
HDMI	IN x2 / OUT x1 (Type A, Version 1.4) IN/OUT x1	
RGB		I X1
LAN	x1 (WOL)	-
RS232C	x1	
HD Base T	x1	-
AUDIO OUT	x1	
Mic IN	x1	
SD Slot	x1	
Wireless	<u>-</u>	
Others		
Built-in Mic	-	
Built-in Speaker	(Operation sound Only)	
Built-in Battery	- "	
Remote Commander	Yes	
Security Lock Slot	Yes	•
Power	DC12V	DC12V
Power Consumption	21W	19W
Dimension	(Set-up) W297 x D482 x H478 mm ((Folded) W297 x D482 x H95 mm
Weight	Approx. 5000g (Main unit)	
Accessories	AC Adapter, USB Cable (version 3.0), Remote Commander, Whiteboard sheet, Instruction Manual	
Accessories		
Optional Accessories		
	Yes by PC	software
Optional Accessories	Yes by PC s Yes by PC s	



CONTACT

ELMO Europe SAS | www.elmoeurope.com

Head Office

12, place de la Defense, Maison de la Defense 92974, Paris La Defense France Tel: +33 (0)1 73 02 67 06

Fax: +33 (0)1 73 02 67 10 info@elmoeurope.com

Middle East Branch

5WA-129, Dubai Airport Free Zone P.O. Box 371556, Dubai United Arab Emirates Tel: +971 (0)4 260 2390 Mob: +971 (56) 477 3475 Fax: +971 (0)4 260 2392 Tariq@elmoeurope.com

PX-10E